



SPECIFICATION

SELENMETALL

SELENIUM METAL – SELENIUM METALLIQUE– SELENIO METALICO

99.5 % Pellets

Selen – Selenium – Sélénium – Selenio.....	99.5 %	min.
Verunreinigungen – Impurities – Impuretés – Impurezas:		
Arsen		
Arsenic – Arsenic – Arsénico	100 ppm	max.
Cadmium		
Cadmium – Cadmium – Cadmio	10 ppm	max.
Kupfer		
Copper – Cuivre – Cobre	50 ppm	max.
Eisen		
Iron – Fer – Hierro	200 ppm	max.
Quecksilber		
Mercury – Mercure – Mercurio	10 ppm	max.
Nickel		
Nickel – Nickel – Niquel	100 ppm	max.
Blei		
Lead – Plomb – Plomo	100 ppm	max.
Tellur		
Tellurium – Tellure – Telurio	1000 ppm	max.
Glührückstand		
Residue of ignition – Résidue involatile – Residuo involátil.....	0.5 %	max.

Änderungen vorbehalten. - This specification may be subject to changes.



SPECIFICATION

SELENMETALL

SELENIUM METAL – SELENIUM METALLIQUE – SELENIO METALICO

99.5 % Pellets

Seite 2 – page 2 – page 2 – página 2

Schüttdichte	
Bulk density - Densité apparente – Densidad aparente	2.5 – 3.0 kg/l
Aussehen	graue Granalien
Appearance – Apparence – Apariencia	grey granules – granules gris – pellets gris
Größe	
Size – Taille – Talla	1 – 5 mm (99 %)
Geruch	ohne
Odour – Odeur – Olor	none – sans – sin
Verpackung	
Packaging – Emballage – Embalaje	25 kg net steel drums with inliner
Transport	
Transportation – Transport – Transporte	not classified according to ADR

Änderungen vorbehalten. - This specification may be subject to changes.