



SPECIFICATION

SELENMETALL

SELENIUM METAL – SELENIUM METALLIQUE– SELENIO METALICO

4N Pellets solar grade

Selen – Selenium – Sélénium - Selenio 99.99 % min.

Verunreinigungen – Impurities – Impuretés – Impurezas:

Arsen

Arsenic – Arsenic – Arsénico 5 ppm max.

Eisen

Iron – Fer – Hierro 10 ppm max.

Quecksilber

Mercury – Mercure – Mercurio 5 ppm max.

Nickel

Nickel – Nickel – Niquel 5 ppm max.

Blei

Lead – Plomb – Plomo 10 ppm max.

Tellur

Tellurium – Tellure – Telurio 5 ppm max.

Änderungen vorbehalten. - This specification may be subject to changes.



SPECIFICATION

SELENMETALL

SELENIUM METAL – SELENIUM METALLIQUE – SELENIO METALICO

4N Pellets solar grade

Seite 2 – page 2 – page 2 – página 2

Schüttdichte	
Bulk density - Densité apparente – Densidad aparente	2.5 – 3.0 kg/l
Aussehen	graue Granalien
Appearance – Apparence – Apariencia	grey granules – granules gris – pellets gris
Größe	
Size – Taille – Talla	1 – 5 mm (99 %)
Geruch	ohne
Odour – Odeur – Olor	none – sans – sin
Verpackung	
Packaging – Emballage – Embalaje	25 kg net steel or 50 kg net fibre drums with inliner, other packaging possible on request
Transport	
Transportation – Transport – Transporte	not classified according to ADR

Änderungen vorbehalten. - This specification may be subject to changes.