

SPECIFICATION

SELENMETALL

SELENIUM METAL – SELENIUM METALLIQUE– SELENIO METALICO

4N5 Pellets high purity

Selen – Selenium – Sélénium - Selenio	99.995 %	min.
Verunreinigungen – Impurities – Impuretés – Impurezas:		
Silber		
Silver – Argent – Plata	0.5 ppm	max.
Arsen		
Arsenic – Arsenic – Arsénico	1 ppm	max.
Cadmium		
Cadmium – Cadmium – Cadmio	0.5 ppm	max.
Kupfer		
Copper – Cuivre – Cobre	0.5 ppm	max.
Eisen		
Iron – Fer – Hierro	3 ppm	max.
Quecksilber		
Mercury – Mercure – Mercurio	0.2 ppm	max.
Nickel		
Nickel – Nickel – Niquel	2 ppm	max.
Blei		
Lead – Plomb – Plomo	0.5 ppm	max.
Tellur		
Tellurium – Tellure – Telurio	5 ppm	max.

Änderungen vorbehalten. - This specification may be subject to changes.

SPECIFICATION

SELENMETALL

SELENIUM METAL – SELENIUM METALLIQUE – SELENIO METALICO

4N5 Pellets high purity

Seite 2 – page 2 – page 2 – página 2

Schüttdichte	
Bulk density - Densité apparente – Densidad aparente	2.5 – 3.0 kg/l
Aussehen	graue Granalien
Appearance – Apparence – Apariencia	grey granules – granules gris – pellets gris
Größe	
Size – Taille – Talla	min. 99 % < 5 mm, max. 2 % < 1 mm
Geruch	ohne
Odour – Odeur – Olor	none – sans – sin
Verpackung	
Packaging – Emballage – Embalaje	25 kg net steel drums with inliner, other packaging possible on request
Transport	
Transportation – Transport – Transporte	not classified according to ADR

Änderungen vorbehalten. - This specification may be subject to changes.